
advisor Documentation

tobe

Oct 18, 2018

Contents:

1	Advisor	1
1.1		1
1.2		1
2		3
2.1	Pip	3
2.2	From Source	3
2.3	Docker	3
2.4	Docker Compose	3
2.5	Kubernetes	4
3		5
4		7
4.1		7
4.2	Docker	7
4.3	Docker Compose	7
4.4	Kubernetes	7
4.5		8
5		9
5.1		9
5.2		9
5.3		9
5.4	Study	9
5.5	Study	9
5.6	Trial	10
6	SDK	11
6.1		11
6.2	Study	11
6.3	Study	12
6.4	Trial	12
6.5		12
6.6		12
6.7	Trial	13

7		15
7.1	YAML	15
7.2	JSON	15

1.1

Advisor is the hyper parameters tuning system for black box optimization.

It is the open-source implementation of [Google Vizier](#) with these features.

- Easy to use with API, SDK, WEB and CLI
- Support abstractions of Study and Trial
- Included search and early stop algorithms
- Recommend parameters with trained model
- Same programming interfaces as Google Vizier
- Command-line tool just like Microsoft NNI.

1.2

- [x] Grid Search
- [x] Random Search
- [x] Bayesian Optimization
- [x] TPE(Hyperopt)
- [x] Random Search(Hyperopt)
- [x] Simulate Anneal(Hyperopt)
- [x] Quasi Random(Chocolate)
- [x] Grid Search(Chocolate)
- [x] Random Search(Chocolate)

- ☒ Bayes(Chocolate)
- ☒ CMAES(Chocolate)
- ☒ MOCMAES(Chocolate)
- ☐ SMAC Algorithm
- ☒ Early Stop First Trial Algorithm
- ☒ Early Stop Descending Algorithm
- ☐ Performance Curve Stop Algorithm

2.1 Pip

```
pip install advisor
```

2.2 From Source

```
git clone git@github.com:tobegit3hub/advisor.git  
cd ./advisor/advisor_client/  
python ./setup.py install
```

2.3 Docker

```
docker run -d -p 8000:8000 tobegit3hub/advisor
```

2.4 Docker Compose

```
wget https://raw.githubusercontent.com/tobegit3hub/advisor/master/docker-compose.yml  
docker-compose up -d
```

2.5 Kubernetes

```
wget https://raw.githubusercontent.com/tobegit3hub/advisor/master/kubernetes_advisor.  
↪yaml  
  
kubectl create -f ./kubernetes_advisor.yaml
```

CHAPTER 3

pip

```
pip install advisor
```

```
advisor_admin server start
```

<http://127.0.0.1:8000>

```
git clone --depth 1 https://github.com/tobegit3hub/advisor.git && cd ./advisor/  
advisor run -f ./advisor_client/examples/python_function/config.json
```

```
advisor study describe -s demo
```


CHAPTER 4

4.1

```
advisor_admin server start
```

4.2 Docker

```
docker run -d -p 8000:8000 tobegit3hub/advisor
```

4.3 Docker Compose

```
wget https://raw.githubusercontent.com/tobegit3hub/advisor/master/docker-compose.yml  
docker-compose up -d
```

4.4 Kubernetes

```
wget https://raw.githubusercontent.com/tobegit3hub/advisor/master/kubernetes_advisor.  
↪yaml  
kubectl create -f ./kubernetes_advisor.yaml
```

4.5

```
git clone --depth 1 https://github.com/tobegit3hub/advisor.git && cd ./advisor/  
pip install -r ./requirements.txt  
./manage.py migrate  
./manage.py runserver 0.0.0.0:8000
```

CHAPTER 5

5.1

```
advisor_admin server start
```

5.2

```
advisor_admin server stop
```

5.3

```
advisor run -f ./advisor_client/examples/python_function/config.json
```

5.4 Study

```
advisor study list
```

5.5 Study

```
advisor study describe -s demo
```

5.6 Trial

```
advisor trials list
```

6.1

```
client = AdvisorClient()
```

6.2 Study

```
study_configuration = {
    "goal":
        "MINIMIZE",
    "randomInitTrials":
        1,
    "maxTrials":
        5,
    "maxParallelTrials":
        1,
    "params": [
        {
            "parameterName": "gamma",
            "type": "DOUBLE",
            "minValue": 0.001,
            "maxValue": 0.01,
            "feasiblePoints": "",
            "scalingType": "LINEAR"
        },
        {
            "parameterName": "C",
            "type": "DOUBLE",
            "minValue": 0.5,
            "maxValue": 1.0,
            "feasiblePoints": "",
```

(continues on next page)

(continued from previous page)

```

        "scalingType": "LINEAR"
    },
    {
        "parameterName": "kernel",
        "type": "CATEGORICAL",
        "minValue": 0,
        "maxValue": 0,
        "feasiblePoints": "linear, poly, rbf, sigmoid, precomputed",
        "scalingType": "LINEAR"
    },
    {
        "parameterName": "coef0",
        "type": "DOUBLE",
        "minValue": 0.0,
        "maxValue": 0.5,
        "feasiblePoints": "",
        "scalingType": "LINEAR"
    },
]
}
study = client.create_study("Study", study_configuration,
                           "BayesianOptimization")

```

6.3 Study

```
study = client.get_study_by_id(6)
```

6.4 Trial

```
trials = client.get_suggestions(study.id, 3)
```

6.5

```

parameter_value_dicts = []
for trial in trials:
    parameter_value_dict = json.loads(trial.parameter_values)
    print("The suggested parameters: {}".format(parameter_value_dict))
    parameter_value_dicts.append(parameter_value_dict)

```

6.6

```

metrics = []
for i in range(len(trials)):
    metric = train_function(**parameter_value_dicts[i])
    metrics.append(metric)

```

6.7 Trial

```
for i in range(len(trials)):
    trial = trials[i]
    client.complete_trial_with_one_metric(trial, metrics[i])
is_done = client.is_study_done(study.id)
best_trial = client.get_best_trial(study.id)
print("The study: {}, best trial: {}".format(study, best_trial))
```


7.1 YAML

```
name: "demo"
algorithm: "BayesianOptimization"
trialNumber: 10
path: "./advisor_client/examples/python_function/"
command: "./min_function.py"
search_space:
  goal: "MINIMIZE"
  randomInitTrials: 3
  params:
    - parameterName: "x"
      type: "DOUBLE"
      minValue: -10.0
      maxValue: 10.0
```

7.2 JSON

```
{
  "name": "demo",
  "algorithm": "BayesianOptimization",
  "trialNumber": 10,
  "concurrency": 1,
  "path": "./advisor_client/examples/python_function/",
  "command": "./min_function.py",
  "search_space": {
    "goal": "MINIMIZE",
    "randomInitTrials": 3,
    "params": [
      {
        "parameterName": "x",
        "type": "DOUBLE",
```

(continues on next page)

(continued from previous page)

```
        "minValue": -10.0,  
        "maxValue": 10.0,  
        "scalingType": "LINEAR"  
    }  
]  
}  
}
```